

**Sure Water, LLC**  
105 S. State Box #105  
Orem, Utah 84058



**www.surewatertanks.com**  
**info@surewatertanks.com**  
**1-800-797-2207 Phone**

---

## **\*PLEASE READ INSTRUCTIONS\***

### **Tank Cleaning Instructions:**

Your Sure Water Tank ships directly to you from the manufacturing facility. As with all water storage containers your tank will need to be washed before filling. Please follow these simple tank cleaning instructions.

1. Lay the tank over on its side and remove the top lid. It's best to do this on the lawn or driveway. Be careful not to damage the tank fittings.
2. While the tank is on its side, spray water into the tank through the top opening and create a pool of water.
3. Pour in a small amount of bleach (1/4 to 1/3 cup).
4. Roll the tank back and forth on the ground mixing the water and the bleach together while coating the inside of the tank with the water/bleach mixture.
5. Thoroughly rinse the tank, spraying the inside walls and then stand the tank back up to let the remaining water drain completely.

### **Additional Cleaning-**

After a few seasons of water storage you may need to re-clean your tank. The frequency and necessity for this depends entirely on your water quality, storage location, and how often you rotate your water. To check for this, remove the top lid and run your fingers along the inside wall of the tank. If you feel any residue on your fingers left from the inside of the tank, then the tank needs another cleaning. Simply follow the instructions outlined above.

## **Parts Installation:**

Your tank will come with two bulk-head fittings (the black fittings already attached to the tank), two brass spigots, and two brass caps. The spigots and brass caps are shipped separately.

### **Bulk-Head Fittings-**

During the shipping process the black bulk-head fittings may have loosened. Re-tighten the fittings, by hand, as much as possible. NOTE- These fittings tighten counter-clockwise. You cannot over-tighten these fittings and the use of a large wrench is acceptable but not necessary.

### **Spigot Installation-**

The spigots come to you already wrapped in Teflon tape. This Teflon tape helps seal the threads between the brass spigot and the plastic bulk-head fitting. The spigots are simply installed and tightened by hand. BE CAREFUL not to cross-thread the spigots. If the spigot being installed is not screwing in straight and easy then back it out and start again. Tighten by hand as much as possible. The spigots CAN be over tightened so be careful if you choose to use a wrench. Never hold onto or use a spigot as a handle to carry the tank. The brass caps are screwed on over the spigots after filling.

## **Tank Filling:**

### **Placement-**

Your tank should be placed on level concrete floor. It is preferred that a barrier of some sort is placed between the tank and the floor. In most cases a piece of plywood or a flat plastic mat is used. Do not use a wooden pallet because most pallets are not strong enough to hold the weight of a full tank.

### **Filling-**

Fill the tank just past the upper spigot and wait for one hour. Check all the fittings to be sure there is no leaking or drips. If everything looks tight then fill the tank the rest of the way. If there are drips from any of the fittings then tighten a 1/4 turn more and wait again.